

## Dry Screed NORIT-TE 20/25

### Product data sheet

#### Description

The NORIT-Dry screed made of gypsum fibre with the unique click system enables an ideal installation result using the NORIT-TE adhesive without additional screwing or stapling. The surface created in this way serves as a load-distributing layer to accommodate all common floor coverings.

#### Advantages

- Extremely high accuracy of fit
- Quick and easy installation
- No additional screwing necessary
- Building biology tested and recommended board material
- Convenient panel size
- Suitable for damp rooms (water exposure classes W0-I & W1-I)



#### Technical Specifications

<b>Panel thickness</b>	20/25 mm
<b>Density</b>	approx. 1,250 kg/m <sup>3</sup>
<b>Weight</b>	approx. 18.7 kg/element (NORIT-TE 20) approx. 23.4 kg/element (NORIT-TE 25)
<b>Building material class</b>	A1 (DIN EN 13501-1)
<b>Product standard</b>	DIN EN 14190
<b>Panel size</b>	1,200 mm x 600 mm
<b>NORIT-TE-Adhesive</b>	Solvent-free PU adhesive; Open time at 20°C: approx. 30 min; Consumption: approx. 18 g/m <sup>2</sup>

#### Processing

We recommend a circular saw with guide rail for straight cuts or a jigsaw for curves and smaller cut-outs. You can find detailed installation instructions on our website.

#### Delivery / Storage

- 20/25 mm, 60/50 elements/pallet (approx. 1,140/1,185 kg/pallet)
- Store in dry environment
- Store at the installation site for 2 days for acclimatisation

#### Certificates

